

Frame Size G (16-125) Amperes


Product description:

Maximum continuous Ampere rating at 55°C

Standard interrupting capacity catalogue number

Fixed Thermal Magnetic OR Adjustable Thermal / Fixed Magnetic

Ue Maximum 240 V / 415V

Icu 65kA 25kA

Ics 33kA 13kA

Dimensions:	H	W	D
1 Pole	130	25	76.8
2 Pole		75	
3 Pole			
4 Pole		100	

Weight Kgs.	1 Pole	0.40
	2 Pole	0.70
	3 Pole	1.00

FTCG-Frame MCCB 25 kA

Fixed Thermal - Magnetic					
1P	Ref. No.	2P	Ref. No.	3P Fixed	Ref. No.
FTCG1016	F100712	FTCG2016	F100724	FTCG3016	F100736
FTCG1020	F100713	FTCG2020	F100725	FTCG3020	F100737
FTCG1025	F100714	FTCG2025	F100726	FTCG3025	F100738
FTCG1032	F100715	FTCG2032	F100727	FTCG3032	F100739
FTCG1040	F100716	FTCG2040	F100728	FTCG3040	F100740
FTCG1050	F100717	FTCG2050	F100729	FTCG3050	F100741
FTCG1063	F100718	FTCG2063	F100730	FTCG3063	F100742
FTCG1070	F100719	FTCG2070	F100731	FTCG3070	F100743
FTCG1080	F100720	FTCG2080	F100732	FTCG3080	F100744
FTCG1090	F100721	FTCG2090	F100733	FTCG3090	F100745
FTCG1100	F100722	FTCG2100	F100734	FTCG3100	F100746
FTCG1125	F100723	FTCG2125	F100735	FTCG3125	F100747

Adjustable thermal / Fixed Magnetic	
3P adj	Ref. No.
-	-
FTCG3020W	F100749
FTCG3025W	F100750
FTCG3032W	F100751
FTCG3040W	F100752
FTCG3050W	F100753
FTCG3063W	F100754
FTCG3070W	F100755
FTCG3080W	F100756
FTCG3090W	F100757
FTCG3100W	F100758
FTCG3125W	F100759

Accessories:
Shunt Trip / 380 & 240V
Under Voltage Release 38 & 2400V
Auxiliary Contacts
Alarm Switch
Handle Mechanism

Adjustable Rating (0.8 -1.0)
FTCG (80-100) 3100
FTCG (63-80) 3080
FTCG (50-63) 3063
FTCG (40-50) 3050
FTCG (32-40) 3040
FTCG (25-32) 3032
FTCG (20-25) 3025
FTCG (16-20) 3020