

# Frame Size JS (175-250) Amperes

(Adjustable Thermal /Adjustable Magnetic)



Product description:  
 Maximum continuous Ampere rating at 50°C  
 Standard interrupting capacity catalogue number

Adjustable Thermal Magnetic, Changeable Trip Unit  
 Ue Maximum                    240 V /                    415V  
 I<sub>cu</sub>                                65kA                        36kA  
 I<sub>cs</sub>                                65kA                        36kA

Dimensions:	H	W	D
1 Pole	165	105	68
2 Pole			
3 Pole			
4 Pole		140	

Weight Kgs.	1 Pole	2.00
	2 Pole	2.00
	3 Pole	2.00
	4 Pole	2.50

## JS - Frame MCCB 36 kA

1P 3p Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
JS1175	F104115	JS2175	F104119	JS3175	F104123	JS4175	F104127
JS1200	F104116	JS2200	F104120	JS3200	F104124	JS4200	F104128
JS1225	F104117	JS2225	F104121	JS3225	F104125	JS4225	F104129
JS1250	F104118	JS2250	F104122	JS3250	F104126	JS4250	F104130

## JH - Frame MCCB 50 kA

1P 3p Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
JH1175	F104131	JH2175	F104135	JH3175	F104139	JH4175	F104143
JH1200	F104132	JH2200	F104136	JH3200	F104140	JH4200	F104144
JH1225	F104133	JH2225	F104137	JH3225	F104141	JH4225	F104145
JH1250	F104134	JH2250	F104138	JH3250	F104142	JH4250	F104146

Accessories:
Shunt Trip / 240 & 380V
Under Voltage Release 240 & 380V
Auxiliary Switch
Alarm Switch
Handle Mechanism Kit
Electrical Operator / 240V

Changeable Trip Unit (0.7 -1.0)	Ref. No.
JS3250T (250 - 225)	F104147
JS3225T (225- 200)	F104148
JS3200T (200 - 175)	F104149

Fixed Magnetic = 5 In  
 Adjustable Magnetic = (5-10)In