

# Frame Size LG (400-630) Amperes

(Adjustable Thermal /Adjustable Magnetic)



Product description:  
 Maximum continuous Ampere rating at 55°C  
 Standard interrupting capacity catalogue number

Adjustable Thermal Magnetic, changeable trip unit

Ue Maximum	240 V /	415V
I <sub>cu</sub>	85kA	65kA
I <sub>cs</sub>	85kA	65kA

Dimensions:	H	W	D
1 Pole	258	140	104
2 Pole			
3 Pole			
4 Pole		183	

Weight Kgs.	1 Pole	6.10
	2 Pole	6.10
	3 Pole	6.10
	4 Pole	7.30

## FTCLG - Frame MCCB 65 kA<sup>②</sup>

1P 3P Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
FTCLG1500	F101051	FTCLG2500	F101053	FTCLG3500	F101055	FTCLG4500	F101057
FTCLG1630	F101052	FTCLG2630	F101054	FTCLG3630	F101056	FTCLG4630	F101058

## FTCLGH - Frame MCCB 85 kA

1P 3P Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
FTCLGH1500	F101059	FTCLGH2500	F101061	FTCLGH3500	F101063	FTCLGH4500	F101065
FTCLGH1630	F101060	FTCLGH2630	F101062	FTCLGH3630	F101064	FTCLGH4400	F101066

Accessories:
Shunt Trip / 240 & 380V
Under Voltage Release 240 & 380V
Auxiliary Switch
Alarm Switch
Handle Mechanism Kit
Electrical Operator / 240V

changeable Trip Unit (0.8-1.0)	Ref. No.
FTCLG3630T (630 - 500)	F101073
FTCLG3500T (500 - 400)	F101074
FTCLG3400T (400 - 315)	F101075
FTCLG3315T (315 - 250)	F101076
FTCLG3250T (250 - 200)	F101077
FTCLG3200T (200 - 160)	F101078

② Available in 50kA I<sub>cu</sub>=I<sub>cs</sub>

Adjustable Magnetic = (5-10)I<sub>n</sub>

Electronic Trip Unit - Thermal Adjustable = (0.4-1)I<sub>n</sub>  
 - Magnetic Adjustable = (2-10)I<sub>n</sub>