

# Frame Size LH (500-800) Amperes

(Adjustable Thermal /Adjustable Magnetic)



Product description:  
 Maximum continuous Ampere rating at 50°C  
 Standard interrupting capacity catalogue number

Adjustable Thermal Magnetic, changeable trip unit

Ue Maximum	240 V /	415V
I <sub>cu</sub>	85kA	50kA
I <sub>cs</sub>	85kA	50kA

Dimensions:	H	W	D
1 Pole	257	210	104
2 Pole			
3 Pole			
4 Pole		280	

Weight Kgs.	1 Pole	12.50
	2 Pole	12.50
	3 Pole	12.50
	4 Pole	17.50

## LH - Frame MCCB 50 kA

1P 3P Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
LH1500	F104186	LH2500	F104189	LH3500	F104192	LH4500	F104195
LH1630	F104187	LH2630	F104190	LH3630	F104193	LH4630	F104196
LH1800	F104188	LH2800	F104191	LH3800	F104194	LH4800	F104197

Accessories:
Shunt Trip /240&380V
Under voltage Release 240&380V
Auxiliary Switch
Alarm Switch
Handle Mechanism Kit
Electrical operator / 240V

changeable Trip Unit (0.7 -1.0)	Ref. No.
LH3800T (800 - 700)	F104198
LH3700T (700 - 630)	F104199
LH3800T (630 - 500)	F104200

Adjustable Magnetic = (5-10)In

Electronic Trip Unit - Thermal Adjustable = (0.4-1)In  
 - Magnate Adjustable = (2-10)In