

Frame Size G (16-125) Amperes

Product description:
 Maximum continuous Ampere rating at 55°C
 Standard interrupting capacity catalogue number

Fixed Thermal Magnetic OR Adjustable Thermal / Fixed Magnetic

Ue Maximum	240 V /	415V
Icu	65kA	25kA
Ics	33kA	13kA



Dimensions:	H	W	D
1 Pole	123.8	25.4	66.7
2 Pole		50.8	
3 Pole		76.2	

Weight Kgs.	1 Pole	0.40
	2 Pole	0.70
	3 Pole	1.00

FTCG-Frame MCCB 25 kA

Adjustable thermal / Fixed Magnetic

1P	Ref. No.	2P	Ref. No.	3P Fixed	Ref. No.	3P adj	Ref. No.
FTCG1016	F100712	FTCG2016	F100724	FTCG3016	F100736	-	-
FTCG1020	F100713	FTCG2020	F100725	FTCG3020	F100737	FTCG3020W	F100749
FTCG1025	F100714	FTCG2025	F100726	FTCG3025	F100738	FTCG3025W	F100750
FTCG1032	F100715	FTCG2032	F100727	FTCG3032	F100739	FTCG3032W	F100751
FTCG1040	F100716	FTCG2040	F100728	FTCG3040	F100740	FTCG3040W	F100752
FTCG1050	F100717	FTCG2050	F100729	FTCG3050	F100741	FTCG3050W	F100753
FTCG1063	F100718	FTCG2063	F100730	FTCG3063	F100742	FTCG3063W	F100754
FTCG1070	F100719	FTCG2070	F100731	FTCG3070	F100743	FTCG3070W	F100755
FTCG1080	F100720	FTCG2080	F100732	FTCG3080	F100744	FTCG3080W	F100756
FTCG1090	F100721	FTCG2090	F100733	FTCG3090	F100745	FTCG3090W	F100757
FTCG1100	F100722	FTCG2100	F100734	FTCG3100	F100746	FTCG3100W	F100758
FTCG1125	F100723	FTCG2125	F100735	FTCG3125	F100747	FTCG3125W	F100759

Accessories:
Shunt Trip / 380 & 240V
Under Voltage Release 38 & 2400V
Auxiliary Contacts
Alarm Switch
Handle Mechanism

Adjustable Rating
FTCG (80-100) 3100
FTCG (63-80) 3080
FTCG (50-63) 3063
FTCG (40-50) 3050
FTCG (32-40) 3040
FTCG (25-32) 3032
FTCG (20-25) 3025
FTCG (16-20) 3020