

Frame Size K (160-400) Amperes

(Adjustable Thermal /Adjustable Magnetic)



Product description:
 Maximum continuous Ampere rating at 55°C
 Standard interrupting capacity catalogue number
 Adjustable Thermal Magnetic, changeable trip unit
 Ue Maximum 240 V / 415V
 Icu 85kA 50kA
 Ics 85kA 50kA

Dimensions:	H	W	D
1 Pole	258	140	104
2 Pole			
3 Pole			
4 Pole		183	

Weight Kgs.	1 Pole	6.10
	2 Pole	6.10
	3 Pole	6.10
	4 Pole	7.30

FTCK - Frame MCCB 50kA

1P 3p Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
FTCK1315	F101024	FTCK2315	F101026	FTCK3315	F101028	FTCK4315	F101030
FTCK1400	F101025	FTCK2400	F101027	FTCK3400	F101029	FTCK4400	F101031

FTCKH - Frame MCCB 65kA

1P 3p Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
FTCKH1315	F101032	FTCKH2315	F101034	FTCKH3315	F101036	FTCKH4315	F101038
FTCKH1400	F101033	FTCKH2400	F101035	FTCKH3400	F101037	FTCKH4400	F101039

Accessories:
Shunt Trip / 240 & 380V
Under Voltage Release 240 & 380V
Auxiliary Switch
Alarm Switch
Handle Mechanism Kit
Electrical Operator / 240V
Lockable Devices

Changeable Trip Unit	Ref. No.
FTCK3400T (400 - 315)	F101047
FTCK3315T (315- 250)	F101048
FTCK3250T (250 - 160)	F101049
FTCK3160T (160 - 125)	F101050