

Frame Size L (630-800) Amperes

(Adjustable Thermal /Adjustable Magnetic)

Product description:
 Maximum continuous Ampere rating at 55°C
 Standard interrupting capacity catalogue number

Adjustable Thermal Magnetic, changeable trip unit

Ue Maximum	240 V /	415V
Icu	85kA	65kA
Ics	85kA	65kA



Dimensions:	H	W	D
1 Pole	406	210	104
2 Pole			
3 Pole			
4 Pole		280	

Weight Kgs.	1 Pole	11.30
	2 Pole	11.30
	3 Pole	11.30
	4 Pole	14.40

FTCL - Frame MCCB 65 kA^②

1P 3P Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
FTCL1630	F101079	FTCL2630	F101081	FTCL3630	F101083	FTCL4630	F101085
FTCL1800	F101080	FTCL2800	F101082	FTCL3800	F101084	FTCL4800	F101086

FTCLH - Frame MCCB 85 kA

1P 3P Frame	Ref. No.	2P 3P Frame	Ref. No.	3P	Ref. No.	4P	Ref. No.
FTCLH1630	F101087	FTCLH2630	F101089	FTCLH3630	F101091	FTCLH4630	F101093
FTCLH1800	F101088	FTCLH2800	F101090	FTCLH3800	F101092	FTCLH4800	F101094

Accessories:
Shunt Trip /240&380V
Under voltage Release 240&380V
Auxiliary Switch
Alarm Switch
Handle Mechanism Kit
Electrical operator / 240V

changeable Trip Unit	Ref. No.
FTCL3800T (800 - 700)	F101101
FTCL3700T (700 - 630)	F101102
FTCL3630T (630 - 500)	F101103
FTCL3500T (500 - 400)	F101104

② Available in 50kA Icu=Ics