

FTCA Circuit Breakers & FTCHAN Moulded Case Switch

(Fixed Thermal /Fixed Magnetic)

Moulded Case Circuit Breakers

Product description:

Standard	IEC60947-3
Voltage	380-415 VAC
Rating	63,80,100,125,150,175,200,225,250A
Connection type	Cable, Busbar
Cable size	70-120 mm ²
IP rating	IP20
Operation Temperature	-5°C to +60°C
Related Insulation Voltage	600Vac
Impluse Withstand Voltage (Vimp)	2500V
Mounting	Chassis
Weight unpacked	2.30 kg
Catalogue #	FTCA xxx/ FTCHA xxx, FTCHA xxxN

FTCA & FTCHA Thermal Magnetic Breakers, Non-Interchangeable Trip
225 amperes, 240 Volts AC Line and Load Terminals Included

Continuous ampere Rating	22.000 Amperes I.C				44.000 Amperes I.C				
	2 Poles		3 Poles		2 Poles		3 Poles		
	Part No.	Ref.no	Part No.	Ref.no	Part No.	Ref.no	Part No.	Ref.no	
Discount Symbol CB-2									
125	FTCA2125	F102240	FTCA3125	F102245	FTCHA2125	F102250	FTCHA3125	F102255	
150	FTCA2150	F102241	FTCA3150	F102246	FTCHA2150	F102251	FTCHA3150	F102256	
175	FTCA2175	F102242	FTCA3175	F102247	FTCHA2175	F102252	FTCHA3175	F102257	
200	FTCA2200	F102243	FTCA3200	F102248	FTCHA2200	1022F53	FTCHA3200	F102258	
225	FTCA2225	F102244	FTCA3225	F102249	FTCHA2225	F102254	FTCHA3225	F102259	

"FTCAN" & "FTCHAN" Moulded Case Switch

Continuous ampere Rating	22.000 Amperes I.C				44.000 Amperes I.C				
	2 Poles		3 Poles		2 Poles		3 Poles		
	Part No.	Ref.no	Part No.	Ref.no	Part No.	Ref.no	Part No.	Ref.no	
Discount Symbol CB-2									
125	FTCA2125N	F102260	FTCA3125N	F102266	FTCHA2125N	F102272	FTCHA3125N	F102278	
150	FTCA2150N	F102261	FTCA3150N	F102267	FTCHA2150N	F102273	FTCHA3150N	F102279	
175	FTCA2175N	F102262	FTCA3175N	F102268	FTCHA2175N	F102274	FTCHA3175N	F102280	
200	FTCA2200N	F102263	FTCA3200N	F102269	FTCHA2200N	F102275	FTCHA3200N	F102281	
225	FTCA2225N	F102264	FTCA3225N	F102270	FTCHA2225N	F102276	FTCHA3225N	F102282	
250	FTCA2250N	F102265	FTCA3250N	F102271	FTCHA2250N	F102277	FTCHA3250N	F102283	

