

F.T.M.C. TYPE Fixed Earth Leakage Relay Pluse FTCELR



Feature

Sensitivity Ranges 30 mA , 100 mA , 300 mA

Application

- Protection:
- Control Panel
 - Feeder / Motor
 - Generator
 - Transformer
 - Electrical Dist.

Core Balance CT

- ID (internal diameter):
- 35 mm
 - 70 mm
 - 120 mm
 - 210 mm

Specification

Aux. Supply	240V / 110VAC 50/60 Hz (-20% +15 %)
Burden on Aux.	< 3 VA
Set Point	Fixed
Delay	Instantaneous
Relay Contacts	Potential Free Contact (NO&NC) Energize on Trip
Contact Rating	6 Amps / 230 V AC/ 28 V DC
Temp	-20°C to +55 °C
Humidity	< 95% RH (non condensing)
Reset	Auto / Manual (Factory Set)
Dimension	17.5 x 91 x 64 mm (WxLxH) Fixed FTCELR
Mounting	Din (35 mm rail) / 2 x m4 screw
Weight	175 gms -Fixed FTCELR

Earth Leakage Relays Fixed

Description	Sensitivity	Time delay	Width	Quantity per carton	FTC list number	Ref.No.
Earth leakage relay	Fixed 30mA,	Fixed	36mm	1	FTCELR30mA	F101675
	100mA	Fixed		1	FTCELR100mA	F101676
	300mA	Fixed		1	FTCELR300mA	F101677